



FX5624

1U C-M 600MHz Embedded System w/1S, VGA, 6LAN(2Giga-LAN), 2USB and CF/Mini-PCI Socket



Features

- Fanless and low power consumption design
- INTEL CPU (C-M 600MHz, 512KB L2 Cache Inside) and System Chipset (910GML+ICH6)
- One 240-Pin DIMM Socket with 1GB DDR2 RAM (max. 2GB)
- 6 LAN Ports (2 Giga-LAN) for Realtek Chipset
- USB V2.0 Ports (*2)
- One CompactFlash Card Type I/II Socket
- Support Mini-PCI for wireless module (Option)
- One 2.5" SATA or PATA HDD space
- One RS232 with DB9 Connector
- One KB/MS with MiniDIN 6P
- Wall Mount (Option)
- VESA Mount (Option)

Specifications

CPU Board: INTEL Celeron-M 600MHz Low Power CPU Board with 1GB DDR2 RAM

I/O Outlets: 6 RJ45 connectors (4X Realtek RTL8100C Chipset, 10/100 Base-T and 2X Realtek RTL8111C Chipset, 10/100/1000 Base-T)
2 USB connectors
1 RS232 connector
1 Reset button switch
1 DC-In connector

Storage Bay: 1 2.5" PATA or SATA HDD space
1 CompactFlash socket

Power Req.: DC 12~24V Input, 27VA maximum

Operating Temperature: 0°C ~ 50 °C (32°F ~ 122 °F)

LED Indicators: 1 Power/HDD/Status LED, 12 LAN LEDs

Dimensions (W*D*H): 256 x 158 x 44 mm



Optional Item

- FX5501K1 - Wall Mount
- FX5504K1 - VESA Mount

Order Information

Model	Description	Verified OS
FX5624	1U Celeron-M 600MHz Embedded System w/1S, VGA, 6LAN(2Giga-LAN), 2USB and CF/Mini-PCI Socket	Windows 2000/XP, XP Embedded, Linux



FabiaTech Corp.

TEL:886-2-22789586 FAX:886-2-22789575

4F-3, No.18, Lane 609, Chung-Hsin Rd., Sec.5, San-Chung City, Taipei Hsien, Taiwan, R.O.C.

www.fabiatech.com