

IES-U061F and IES-U062F

6 x 10/100TX + 1x 100FX or 2x 100FX Industrial Unmanaged Switch



Highlights

- Rigid Aluminum Case
- Redundant DC Power Input
- Fault Relay
- 6 10/100 TX ports and 1 or 2 MM or SM
- 10/100Mbps- full/Half-duplex, auto-negotiation, Auto-MDI/MDIX
- 2K MAC address and 448 Bits Buffer Memory
- -25 to 70°C operating temperature

Specification

Technology		Environment	
Standards	IEEE 802.3 10Base-T Ethernet	Operating Temperature	-25°C to 70°C
	IEEE 802.3u 100Base-TX/FX Fast Ethernet	Storage Temperature	-40°C to 85°C
	IEEE802.3xFlow Control and Back-pressure	Ambient Relative Humidity	0% to 95%(non-condensing)
Packet Buffer Memory	448 K bits	Regulatory Approvals	
Processing Type	Store-and-Forward	Safety	UL, CUL, CE, EN60950
Address Table Size	2K MAC addresses	EMI	FCC Part 15
Interface		EMS	EN61000-4-2 (ESD), EN61000-4-3 (RS), EN61000-4-4 (EFT), EN61000-4-5 (Surge), Level 3, EN61000-4-6 (CS), Level 3
LED Indicators	Power (Green) X 2		
	RJ45 Port: Link/Activity. Fiber Port: Link/Activity		
	Alarm: Port/Power Event (Red On)		
RJ45 Ports	6 x 10/100 Base-T(X), Auto MDI/MDIX		
Fiber Ports	1 or 2 x100FX SC- MM or SM	Shock	IEC60068-2-27
Terminal Block	Removable 9-pin Terminal Block	Free Fall	IEC60068-2-32
Power		Vibration	IEC60068-2-6
Input	24VDC (12 to 48 VDC), redundant inputs, Reverse Polarity Protection		
Power Consumption	12 W Max.		
Mechanical			
Casing	IP 30 Protection Aluminum Case		
Dimensions	55mm(W)x108mm(D)x120mm(H)		
Installation	DIN-Rail(Standard), Wall Mount(Option)		

Ordering information

IES-U061F(SC/MM)	6 10/100TX + 1* 100FX SC, 2KM, Industrial Switch,-25C to 70C
IES-U061F(SC/SM 30)	6 10/100TX + 1* 100FX SC, Single Mode 20KM, Industrial Switch,-25C to 70C
IES-U062F(SC/MM)	6 10/100TX + 2* 100FX SC, 2KM, Industrial Switch,-25C to 70C
IES-U062F(SC/SM 30)	6 10/100TX + 2* 100FX SC, Single Mode 20KM, Industrial Switch,-25C to 70C