



VScom USB-COMi SI-M

USB to 1 RS422/485 port adapter (Isolated)



KEY FEATURES

- DIN-Rail mountable
- 1 x RS 422/485 port
- Terminal block
- Optical isolated
- Speed up to 921.6kbps
- No external power supply
- Metal case

Overview

Serial ports on USB allow further use of existing devices, even when the computer doesn't offer serial ports.

The high speed serial port with the 128 byte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.



Specifications

| | |
|--------------------|--|
| Serial interface | RS 422/485 port, optical isolated |
| Ports | 1 |
| Speed | Up to 921.6kbps |
| RS 422/485 signals | RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND RS485 Data+/-, GND |
| Power | USB Bus powered, no external power supply |
| Driver | Windows 98, ME, 2000, XP, 2003 Server, Vista Linux (Kernel 2.4 and up built-in) |
| Connectors | 1 DB9 male and terminal block |
| Dimensions | 57 x 72 x 22 mm (W×L×H) 82 x 77 x 22 mm with DB9 connector and ears |

Ordering Information

| | |
|----------------------|--|
| Art. No | 639 |
| Product Name | VScom USB-COMi SI-M |
| Packing List | VScom USB-COMi SI-M, USB cable 0,9m, CD, English Documentation |
| Optional Accessories | DK 35A - DIN-Rail mounting kit |